

### Physical Properties

Configuration	3PP-PR-B
Type	Insert (IN)
Setup	Standalone (STA)
Curvature	6x (Mat101)
Finish	Textile
Thickness (mm)	32,3 ± 3
AD (kg/m <sup>2</sup> )	26,7 ± 2,1

*Other surface finishes available*

### Standard Sizes

Size	Dimensions (mm)	Area (cm <sup>2</sup> )	Weight (g)
SAPI-XS	292x184-076x044	500	1350 ± 140
SAPI-S	298x222-078x053	620	1660 ± 170
SAPI-M	317x241-083x057	720	1920 ± 190
SAPI-L	337x260-087x060	820	2200 ± 220
SAPI-XL	356x280-092x067	940	2500 ± 250
NATO-XS	276x191-081x052	490	1300 ± 130
NATO-S	282x230-084x062	600	1590 ± 160
NATO-M	300x250-089x067	690	1850 ± 190
NATO-L	319x270-093x071	800	2130 ± 220
NATO-XL	337x290-099x079	900	2400 ± 240
Side M	150x150 (R400)	225	600 ± 60
Side L	200x150 (R400)	300	800 ± 80

*More sizes and cuts available on demand*

### Applicable standards or Procedures

NIJ-STD-0101.06 - Level III Modified

Caliber	Payload	Ammunition Reference	Shots	Velocity (m/s)	BFS (mm)
5,56x45	SS109	VPAM APR06	6	950	< 44
7,62x39	MSC	NIJ-0101.07	6	730	< 44
7,62x51	M80	NIJ-0101.06	6	847	< 44

*This list may not include all threats this product can defeat*



Green tip + AK47 Rated



Maximum Coverage



Made in Lithuania



EU/US materials